

CORE 400° - Asphalt Release Agent



PRODUCT #: KPC-307622

CHARACTERISTICS:

Appearance: Light Green Liquid
 Odor: Characteristic
 pH: 9
 Specific Gravity: 1.02
 Weight: 8.50
 Viscosity: Water Like
 Flash Point: Greater than 400° F
 Dilution: 1:10

ADVANTAGES:

CORE 400° is an Industrial-grade soap surface protectant and asphalt release agent. It is a concentrated blend of biodegradable soap and detergents designed to coat all surfaces that may come in contact with asphalt. It is used in setting free asphalt which may come in contact with truck beds and equipment.

DIRECTIONS:

Mix 1 gallon of product with 10 gallons of water and apply as a thick foam through a foaming device. For the beds of trucks carrying asphalt, apply liberally to the truck bed. May be used in stronger concentrations if desired to increase residual effect. To prevent adhesion of mix to equipment or hand tools, apply the solution by spray or immersion. Will not affect asphalt or vehicles.

PRECAUTIONS:

Inhalation: None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFO:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - Not Regulated



AVAILABLE IN:

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck



GUARANTEE:

KCP Industries manufacturing and laboratory controls ensure uniform quality throughout our product line. All Kish manufactured products are guaranteed for 1 year when used as directed.