

BIOKOTE-EF125 is a ready-to-use form release agent that should be applied to clean forms free of dirt and debris. Stir before use. Prior to coating plywood forms, apply one or two heavy brush coats to edges for waterproofing protection. Apply in a thin uniform film with a sprayer, brush, or roller. No special application equipment is necessary; however we do recommend a spray applicator. Runs or puddles need to be brushed out or wiped up. Refer to technical data sheet for further product info and application.

Safety Instructions

Always use precaution when handling chemical products. We recommend using rubber gloves, safety glasses and apply this product in a well ventilated area.

Recommended Storage Conditions

When storing containers for long periods of time store in a cool dry environment.

Shelf Life 3 years in original containers



GALLONS

NET CONTENTS



Health Hazard Data, Effects of Overexposure, First Aid

Skin: Contact of this product upon the skin may cause slight irritation. Flush exposed area with water. If irritation persists, consult physician immediately. **Eyes:** Contact of this product upon the eyes will cause irritation of the eyes and eye lids. Flush eyes for 30 minutes with water. If irritation persists, consult physician immediately.

Inhalation: Fumes from this product are considered non-toxic. Remove patient to clean atmosphere.

Ingestion: When concentrated solution of this product are swallowed, it can cause slight irritation of the mouth, esophagus and stomach. Do not induce vomiting. Have patient drink large amounts of water. Consult physician immediately.

Carcinogens: Product contains no known carcinogens.



